




Installation Method



Non Directional Quarter turn Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Natural Stones **Colour** Cool Impala Marble **Collection** Level Set Collection

Product Specifications

Product Number	A001
Product Construction	High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55
Total Thickness	(EN ISO 24346) 4.5mm
Total Weight	6880 g/m ²
Packaging	2.5 m ²
Backing	Sound Choice™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	DOP PBRG-AHCK3R
UKCA Declaration of Performance	DOP PBRG-AHCK3R
Castor Chair Rating	ISO 4918 Pass
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	40.00
Light Reflectance Value (LRV-Y)	11.00
Curling	(ISO 23999) ≤ 2 mm
Flexibility	(EN ISO 24344) Method A - Pass
Abrasion Resistance	(EN 660-2) Group T
Residual Indentation	(EN ISO 24343-1) ≤ 0.2
Determination of Anti-Slip	(DIN 51130) R9
Pendulum Dry 4S	36+ (BS 7976-2) Low slip potential
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	16 dB

Environmental Specifications

Total Recycled Content	39 %
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT
Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m ²
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

Technical Informations

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines
Warranty	15 years LVT