




Installation Method



Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product UR101 **Colour** Ash/Ivy **Collection** Urban Retreat Collection
Backing CQuest™Bio

Product Specifications

Product Construction	Tapestry Tufted Patterned Structured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
Packaging	4m ² Box
Optional Backings	ReCushion Bac®

More Product Specifications

Pile Yarn Weight	851.00 g/m ² ± 5%
Total Weight	4,419 g/m ² ± 5%
Pile Height	2.60 mm +15% / - 10%
Total Thickness	8.5 mm ±0.5mm
Gauge - Ends per 10 cm	1/10 - 39.4
Tufts per m ²	114260 /m ² ±5%

Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	BS-EN 985 r ≥ 2.4
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	41.90
Light Reflectance Value (LRV-Y)	12.40
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	26 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.2
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.04
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.05
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.09
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.22
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.45
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.58

Environmental Specifications

Total Recycled Content	84 %
Pre-Consumer (Total)	74.40 %

Post-Consumer (Total)	9.60 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	8.57 %
Total Recycled & Bio Based Content	92.57 %
Indoor Air Quality	French A+ GLP 100209 M1 Emission Certification -CQB
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	3.43 kg CO ₂ eq./m ²
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Waste	Non-directional – 1-2%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe