



Installation Method



Ashlar Monolithic Non Directional



Quarter Turn Brick

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Walk On By **Colour** A01501 Polychrome

Product Specifications

| | |
|----------------------|-------------------------------------------------------------------------------|
| Product Number | A015 |
| Product Construction | High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content |
| Finish | Ceramor™ - UV Stabilised Ceramic Bead Coating |
| Wear Layer Thickness | (EN ISO 24340) 0.55 mm |
| Total Thickness | (EN ISO 24346) 4.5mm |
| Total Weight | (EN ISO 23997) 6880 g/m ² |
| Size – Packaging | 50cm x 50cm |
| Backing | Sound Choice™ Acoustic Backing |

Performance Specifications

| | | |
|-----------------------------------------------------------|----------------------------------------------------------------|---------------|
| Wear Classification | EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial | |
| CE Declaration Of Performance | DOP PBRG-AHCK3R | |
| UKCA Declaration of Performance | DOP PBRG-AHCK3R | |
| Castor Chair Rating | (ISO 4918 / EN425) Pass | |
| Flammability | (EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1) | |
| Light Fastness | ≥7 (ISO 105-B02) | |
| Light Reflectance Value (LRV) | LRV – L value | LRV – Y value |
| | 71.95 | 43.58 |
| Dimensional Stability | (ISO 23999) ≤ 0.25% | |
| Curling | (ISO 23999) ≤ 2 mm | |
| Flexibility | (EN ISO 24344) Method A - Pass. | |
| Abrasion Resistance | (EN 660-2) Group T | |
| Residual Indentation | mm(EN ISO 24343-1) ≤ 0.2 | |
| Determination of Anti-Slip | (DIN 51130) R10 | |
| Chemical Resistance | (EN ISO 26987) Very Good | |
| Impact Sound Insulation ΔL _w EN ISO 10140-3 | 16 dB | |

Environmental Specifications

| | |
|---------------------------------------|----------------------------------------------------------------------------------------|
| Total Recycled Content | 39% |
| Indoor Air Quality | Indoor Air Comfort GOLD® |
| | French A+ |
| | M1 Emission Certification - LVT LVT Greenguard Gold |
| Potential Green Building Contribution | |
| Environmental Product Declaration | MR-ULE-EPD-INF-20170001-EN |
| Full Life Cycle Carbon Footprint | According to EPD or EPD calculation method |
| Embodied Carbon (Cradle to Gate) | 9.2 kg CO ₂ eq./m ² |
| Full Life Cycle Carbon | Certified Carbon Neutral Floors™ |
| End of Life Options | |
| ReUse | Can be cleaned and reused in a non-critical location to extend its useful life. |
| Fully Recyclable | Can be recycled into carpet tile backing. |
| Material Composition | Free of Ortho Phthalates |

Technical Information

| | |
|--------------|-------------------------------------------------------------|
| Installation | See recommended LVT installation guidelines |
| Maintenance | See recommended LVT maintenance guidelines |
| Warranty | 15 years LVT |

Performance Qualifications



Certifications

| | |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------|
|  | |
| 17 | |
| Interface European Manufacturing B.V. Industrielaan 15 3925 BD Scherpenzeel The Netherlands | |
| DOP PBRG – AHCK3R | |
| EN 14041:2004 Notified Body - 0493 | |
| Resilient floor covering for internal use. | |
| Classification | Class 33/42 (EN ISO 10874) |
| Reaction to fire | Class Bfl-s1 (see EN 14041, clause 4.1) |
| Slip resistance | Class DS (See EN 14041, clause 4.5) |
| Formaldehyde | E1 (see EN 14041, clause 4.3) |
| Anti-static | <2.0kV (See EN14041, clause 4.6.1) |
| www.interface.com/lvt-emea | |

| | |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------|
|  | |
| 21 | |
| Interface European Manufacturing B.V. Industrielaan 15 3925 BD Scherpenzeel The Netherlands | |
| DOP PBRG – AHCK3R | |
| EN 14041:2004 Approved Body - 0321 | |
| Resilient floor covering for internal use. | |
| Classification | Class 33/42 (EN ISO 10874) |
| Reaction to fire | Class Bfl-s1 (see EN 14041, clause 4.1) |
| Slip resistance | Class DS (See EN 14041, clause 4.5) |
| Formaldehyde | E1 (see EN 14041, clause 4.3) |
| Anti-static | <2.0kV (See EN14041, clause 4.6.1) |
| www.interface.com/lvt-emea | |

