

OBJECT CARPET

Typical characteristics

Name of article	AT-Poodle 1400
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 50x50
Surface structure ISO 2424	Shag
Colourways	Uni
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Welltex® Acoustic
Overall weight ISO 8543	approx. 3050 g/m ²
Overall thickness ISO 1765	approx. 11,0 mm
Pile service weight	approx. 1400 g/m ²



Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC5

Ecological characteristics

Conformity certificate	1658-CPR-3497
DOP	1060 OC 3497
EPD (Environmental Product Declaration)	EPD-GUT-20160118-CCA1-EN
Prodis-ID	98547C8F

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com