




Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Cliff **Colour** Limestone **Collection** Fresco Valley Collection

Product Specifications

Product Number	A024
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	CERAMOR+™ UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55
Total Thickness	(ASTM F386) Passes
Total Weight	6,880 g/m ²
Size	25cm x 1m
Tiles per Box	10 - 2.5m ²
Backing	Sound Choice™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	DOP PBRG-AHCK3R
UKCA Declaration of Performance	DOP PBRG-AHCK3R
Castor Chair Rating	(ISO 4918 / EN425) Pass
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Dimensional Stability	(ISO 23999) ≤ 0.25 %
Curling	≤ 2 mm (ISO 23999)
Flexibility	(EN ISO 24344) Method A - Pass
Abrasion Resistance	(EN 660-2) Group T
Residual Indentation	≤0.2mm
Determination of Anti-Slip	R10 (EN 16165 - Annex B)
Pendulum Dry 4S	36+ Low Slip Potential (EN 16165 - Annex C)
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	16 dB


Environmental Specifications

Environmental Product Declaration	Download EPD
Total Recycled Content	39 %
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT
Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m ²
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

Technical Information

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines

Certifications



EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial



(ISO 4918 / EN425) Pass



(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)



≥ 7



(ISO 23999) ≤ 0.25 %



(EN ISO 24344) Method A - Pass



$\leq 0.2\text{mm}$



(EN 660-2) Group T



(EN ISO 26987) Very Good



Yes



Yes



French A+



0.03

CE

17

Interface European Manufacturing B.V.
Industriestraat 15
5255 BD
Schijndorp
The Netherlands

DOP PSB2G - A1CKGR

EN 14041:2004

Notified Body - 0459

Relevant for covering for installation

Classification: Class B242 (EN ISO 10241)

Reaction to fire: Class B242 (EN ISO 10241, class 1)

Spontaneous Combustion: Class D3 (EN ISO 14041, class 4.0)

Flammability: Class E1 (EN ISO 14041, class 4.0)

Acoustic: < 2.0Kv (EN ISO 14041, class 4.0)

www.interface.com/Interface

LVT

**UK
CA**

21

Interface European Manufacturing B.V.
Industriestraat 15
5255 BD
Schijndorp
The Netherlands

DOP PSB2G - A1CKGR

EN 14041:2004

Approved Body - 0221

Relevant for covering for installation

Classification: Class B242 (EN ISO 10241)

Reaction to fire: Class B242 (EN ISO 10241, class 1)

Spontaneous Combustion: Class D3 (EN ISO 14041, class 4.0)

Flammability: Class E1 (EN ISO 14041, class 4.0)

Acoustic: < 2.0Kv (EN ISO 14041, class 4.0)

www.interface.com/Interface

LVT